

**Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,)
Carbon Monoxide (0.0005 - 0.09%,) Hydrogen
Sulfide (0.001 - 0.025%) in Nitrogen Balance**

Safety Data Sheet 50300 / PN 3489

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 07/01/2015

Revision date: 12/12/2017

Supersedes: 07/01/2015

Version: 1.1

SECTION 1: Identification**1.1. Identification**

Product form : Mixtures
Product name : Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance
ISC Part No. : 1810-6179, 1810-7219, 1810-9094, 1810-9177, 1810-9188, 1810-9197, 1810-9348, 1810-9245

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Supplier

U.S. Supplier: Industrial Scientific Corporation
1 Life Way
Pittsburgh, PA 15205-7500
Phone (412) 788-4353
TOLL-FREE 800-DETECTS
Fax (412) 788-8353

MANUFACTURER: CALGAZ
821 Chesapeake Drive
Cambridge, MD 21613

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300
Internationally: 1-703-527-3887

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Gases under pressure : Compressed gas H280 Contains gas under pressure; may explode if heated.
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labelling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H280 - Contains gas under pressure; may explode if heated.
OSHA-H01 - May displace oxygen and cause rapid suffocation
CGA-HG16 - Extended exposure to gas reduces the ability to smell sulfides.
Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P403 - Store in a well-ventilated place.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52 °C/125 °F
CGA-PG05 - Use a back flow preventive device in the piping

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen

Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG21 - Open valve slowly
CGA-PG29 - Do not depend on odor to detect presence of gas

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Nitrogen	(CAS-No.) 7727-37-9	79.295 – 99.8975	Press. Gas (Comp.), H280
Oxygen	(CAS-No.) 7782-44-7	0.001 – 19.49	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Propane	(CAS-No.) 74-98-6	0.1 – 1.1	Simple Asphy Flam. Gas 1, H220 Press. Gas (Liq.), H280 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Carbon Monoxide	(CAS-No.) 630-08-0	0.0005 – 0.09	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Repr. 1A, H360 STOT RE 1, H372
Hydrogen Sulfide	(CAS-No.) 7783-06-4	0.001 – 0.025	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/effects after skin contact : Adverse effects not expected from this product.

Symptoms/effects after eye contact : Adverse effects not expected from this product.

Symptoms/effects after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/effects upon intravenous administration : Not known.

Most important symptoms and effects, both acute and delayed : No effect on living tissue. Refer to section 11.

Chronic symptoms : Adverse effects not expected from this product.

4.3. Immediate medical attention and special treatment, if necessary

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Hazardous combustion products : None known

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g. Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.
- Specific methods : Exposure to fire may cause containers to rupture/explode. Continue water spray from protected position until container stays cool. Move containers away from the fire area if this can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.
- Emergency procedures : Evacuate personnel to a safe area. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g. Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

- Try to stop release if without risk.

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if without risk.
- Methods for cleaning up : Dispose of contents/container in accordance with local/regional/national/international regulations.
- Methods and material for containment and cleaning up : None.

6.4. Reference to other sections

- See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not pierce or burn, even after use. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
- Safe handling of the gas receptacle : Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safe use of the product	: Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Hygiene measures	: Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, including any incompatibilities	
Technical measures	: Comply with applicable regulations.
Storage conditions	: Do not expose to temperatures exceeding 52 °C/ 125 °F. Keep container closed when not in use. Protect containers from physical damage; do not drag, roll, slide or drop. Store in well ventilated area.
Incompatible products	: None known.
Incompatible materials	: None known.
Conditions for safe storage, including any incompatibilities	: Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
Storage area	: Store away from heat. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance	
No additional information available	
Oxygen (7782-44-7)	
No additional information available	
Nitrogen (7727-37-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Nitrogen
Remark (ACGIH)	Simple Asphyxiant
ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Carbon Monoxide (630-08-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	25 ppm
USA - ACGIH - Biological Exposure Indices	
Biological Exposure Indices (BEI)	3.5 % of hemoglobin Parameter: Carboxyhemoglobin - Medium: blood - Sampling time: end of shift (background, nonspecific) 20 ppm Parameter: Carbon monoxide - Medium: end-exhaled air - Sampling time: end of shift (background, nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m³)	55 mg/m³
OSHA PEL (TWA) (ppm)	50 ppm
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	1200 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m³)	40 mg/m³
NIOSH REL (TWA) (ppm)	35 ppm
NIOSH REL (ceiling) (mg/m³)	229 mg/m³
NIOSH REL (ceiling) (ppm)	200 ppm

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane (74-98-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Propane
Remark (ACGIH)	Simple Asphyxiant
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL (TWA) (mg/m³)	1800 mg/m³
OSHA PEL (TWA) (ppm)	1000 ppm
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	2100 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m³)	1800 mg/m³
NIOSH REL (TWA) (ppm)	1000 ppm
Hydrogen Sulfide (7783-06-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	1 ppm
ACGIH STEL (ppm)	5 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (Ceiling) (ppm)	20 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	50 ppm Peak (10 minutes once, only if no other measurable exposure occurs)
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	100 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (ceiling) (mg/m³)	15 mg/m³
NIOSH REL (ceiling) (ppm)	10 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits (where available). Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand protection

Eye protection:

Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing, e.g. lab coats, coveralls or flame resistant clothing.

Respiratory protection:

None necessary during routine operations. See Sections 5 & 6

Thermal hazard protection:

None necessary during routine operations.

Other information:

Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Colour	: Colourless
Odour	: Rotten eggs
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Similar to air
Solubility	: Water: No data available
Partition coefficient n-octanol/water (Log Pow)	: Not applicable for gas mixtures. Not applicable for gas mixtures.
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not applicable (non-flammable gas).
Oxidising properties	: None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	800000 ppm/4h
Nitrogen (7727-37-9)	
LC50 inhalation rat (ppm)	820000 ppm/4h
Carbon Monoxide (630-08-0)	
LC50 inhalation rat (ppm)	1880 ppm/4h
Propane (74-98-6)	
LC50 inhalation rat (ppm)	282800 ppm/4h
Hydrogen Sulfide (7783-06-4)	
LC50 inhalation rat (mg/l)	700 mg/m ³ (Exposure time: 4 h)
LC50 inhalation rat (ppm)	356 ppm/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Hydrogen Sulfide (7783-06-4)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Carbon Monoxide (630-08-0)	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Symptoms/effects after inhalation : May displace oxygen and cause rapid suffocation.
Symptoms/effects after skin contact : Adverse effects not expected from this product.
Symptoms/effects after eye contact : Adverse effects not expected from this product.
Symptoms/effects after ingestion : Ingestion is not considered a potential route of exposure.
Symptoms/effects upon intravenous administration : Not known.
Most important symptoms and effects, both acute and delayed : No effect on living tissue. Refer to section 11.
Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

Carbon Monoxide (630-08-0)	
LC50-96 h - fish [mg/l]	Study scientifically unjustified.
EC50 48h - Daphnia magna [mg/l]	Study scientifically unjustified.

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Monoxide (630-08-0)	
EC50 72h Algae [mg/l]	Study scientifically unjustified.
Propane (74-98-6)	
LC50-96 h - fish [mg/l]	49.9 mg/l
EC50 48h - Daphnia magna [mg/l]	27.1 mg/l
EC50 72h Algae [mg/l]	11.9 mg/l
Hydrogen Sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50-96 h - fish [mg/l]	0.007 – 0.019 mg/l
EC50 48h - Daphnia magna [mg/l]	0.12 mg/l
EC50 72h Algae [mg/l]	1.87 mg/l

12.2. Persistence and degradability

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance	
Persistence and degradability	No data available.
Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.
Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.
Carbon Monoxide (630-08-0)	
Persistence and degradability	Will not undergo hydrolysis. Not readily biodegradable. Not applicable for inorganic products
Propane (74-98-6)	
Persistence and degradability	No data available.
Hydrogen Sulfide (7783-06-4)	
Persistence and degradability	Not applicable for inorganic products

12.3. Bioaccumulative potential

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for gas mixtures.
Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas mixtures.
Bioaccumulative potential	No data available.
Oxygen (7782-44-7)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
Bioaccumulative potential	No ecological damage caused by this product.
Nitrogen (7727-37-9)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
Bioaccumulative potential	No ecological damage caused by this product.
Carbon Monoxide (630-08-0)	
Partition coefficient n-octanol/water (Log Pow)	1.78
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	2.36
Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas mixtures.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Hydrogen Sulfide (7783-06-4)	
BCF fish 1	Bioaccumulation unlikely

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen Sulfide (7783-06-4)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance	
Mobility in soil	No data available
Oxygen (7782-44-7)	
Ecology - soil	No ecological damage caused by this product.
Nitrogen (7727-37-9)	
Ecology - soil	No ecological damage caused by this product.
Carbon Monoxide (630-08-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Propane (74-98-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
Hydrogen Sulfide (7783-06-4)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.

Product/Packaging disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport Document Description : UN1956 Compressed gas, n.o.s. (Oxygen ; Nitrogen), 2.2

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.
Oxygen ; Nitrogen

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg
CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transportation of Dangerous Goods

Transport by sea

Transport Document Description (IMDG) : UN 1956 Compressed gas, n.o.s. (Oxygen ; Nitrogen), 2
UN-No. (IMDG) : 1956
Proper Shipping Name (IMDG) : Compressed gas, n.o.s.
Class (IMDG) : 2 - Gases
Limited quantities (IMDG) : 120 ml

Air transport

Transport Document Description (IATA) : UN 1956 Compressed gas, n.o.s. (Oxygen ; Nitrogen), 2.2
UN-No. (IATA) : 1956
Proper Shipping Name (IATA) : Compressed gas, n.o.s.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Oxygen (7782-44-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Nitrogen (7727-37-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Carbon Monoxide (630-08-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Propane (74-98-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Hydrogen Sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
Section 302 EPCRA Reportable Quantity (RQ)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

15.2. International regulations

CANADA

Oxygen (7782-44-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Nitrogen (7727-37-9)	
Listed on the Canadian DSL (Domestic Substances List)	

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Monoxide (630-08-0)
Listed on the Canadian DSL (Domestic Substances List)
Propane (74-98-6)
Listed on the Canadian DSL (Domestic Substances List)
Hydrogen Sulfide (7783-06-4)
Listed on the Canadian DSL (Domestic Substances List)
EU-Regulations
Oxygen (7782-44-7)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Nitrogen (7727-37-9)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Carbon Monoxide (630-08-0)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Propane (74-98-6)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Hydrogen Sulfide (7783-06-4)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
National regulations
Oxygen (7782-44-7)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Nitrogen (7727-37-9)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Carbon Monoxide (630-08-0)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Propane (74-98-6)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen Sulfide (7783-06-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on KECL/KECI (Korean Existing Chemicals Inventory)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Carbon Monoxide (630-08-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Component	State or local regulations
Oxygen(7782-44-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Nitrogen(7727-37-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Carbon Monoxide(630-08-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List
Propane(74-98-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Hydrogen Sulfide(7783-06-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/12/2017

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-statements:

H220	Extremely flammable gas.
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Oxygen (0.001 - 19.49%,) Propane (0.1 - 1.1%,) Carbon Monoxide (0.0005 - 0.09%,) Hydrogen Sulfide (0.001 - 0.025%) in Nitrogen Balance

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this gas mixture. To the best of Calgaz's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.